

Specifications Nazca Gaucho Tour 24" / 26" / 28"

status April 17, 2019
Changes and errors in the prices and specifications are strictly reserved

| | |
|-------------------------|---|
| Seat height | Gaucho 24" / 26" / 28": resp. 56 / 62 / 64 cm (shock in middle position, loaded, without front suspension). |
| Crank height | Gaucho 24" / 26" / 28": resp. 72 / 78 / 80 cm (shock in middle position, loaded, without front suspension). |
| Wheelbase | Gaucho 24" / 26" / 28": resp. 112 / 113 / 114 cm |
| Wheelsize | 24" (ETRTO 507 mm – max tire width 50 mm) // 26" (ETRTO 559 mm – max tire width 50 mm) 28" (ETRTO 622 mm – max width 40 mm) |
| Seat angle | adjustable between 26 – 34 degrees, with quick-releases |
| Weight | From ca.18 kg, depending on specification and options |
| Material frame | Frame/rear fork 25CrMo4, front tube/ connecting plates aluminium |
| Standard access. | Alu travel rack, mud-guards, LED rear light, chain tubes |
| Standard colours | firedred, applegreen, nightblue, black satin, melon yellow, white |
| Warranty | 1 year on parts, 3 years on coating, 5 years on frame. |

Technical data

| | Allround 3 x 9 Dual Drive | Allround 3 x 10 Deore | Top-touring 3 x 10 Deore XT | Shimano Alfine 11 speed | Rohloff Speedhub 500/14 |
|-------------------------------------|---|---|-----------------------------------|---|----------------------------|
| Tires | Gaucho 2 x 24": Schwalbe Marathon HS420, 47 mm Gaucho 2 x 26": Schwalbe Marathon HS420, 40 mm Gaucho 2 x 28": Schwalbe Marathon HS420, 37 mm | | | | |
| Brakes | Avid BB7 mechanical disc brakes, Avid SD7 levers | | | | |
| Hubs 32 spokes | Shimano Deore | | Shimano XT M8000 | Shimano Deore | |
| | front | Dual Drive Premium 3 | | Shim. Deore | Alfine SG-700S |
| Rear shock | DNM DV-22AR, adjustable rebound, steel spring | | | | |
| Front derailleur | - | Deore - M591 | Deore XT M8000 | - | - |
| Rear derailleur | SRAM X7 | Shimano Deore M6000 | Deore XT M781/10 | Alfine chain tensioner | Rohloff chain tensioner |
| Shifters | SRAM X7 twist shifters | Deore SL-M6000 trigger shifters | Deore XT SL-M780 trigger shifters | Alfine trigger shifter SL-S700 | Rohloff Twist shifter |
| Crankset, bracket integrated | FC-S501 39 or 45t. + chain guard | Shimano Deore FC-T6010 48/36/26 + chain guard | | Shimano Alfine FC-S501 39 or 45t. + chain guard | |
| Cassette | HG50 12-25 // 11-34 /9 speed | HG50 11-34/ 10 speed | M771 11-34 / 10speed | 20t. | 16t. |
| Chain | KMC X9-73G | KMC-X10-93S | | KMC X8-93S | |
| Front fork | CrMo steel (option front suspension only for 26" ASS and AERO) 1 1/8" | | | | |
| Seat/cushion | Material seat glasfiber/epoxy, seat type <i>Sport</i> (sizes M, L, XL) or seat type <i>Comfort</i> (sizes M, M/L, L with cushion type <i>Comfort</i> (Nazca) or <i>Sport</i> (Novosport)) | | | | |

Prices Nazca Gaucho Tour (Steering options: USS, ASS, Aero)

Prices in Euro's,
incl.21% VAT, excl.
Shipping costs

| | |
|--|------|
| 3 x 9 Allround, SRAM Dual Drive 3 | 2695 |
| 3 x 10 Allround, Shimano Deore | 2745 |
| 3 x 10 Top touring, Shimano Deore XT-10 speed | 2895 |
| 11 sp. Shimano Alfine speedhub | 2895 |
| 14 sp. Rohloff speedhub 500/14 | 3995 |
| Framekit (consists of: frame complete, rear shock, front fork, seat with supports, steerer complete, chain idlers and tubes, luggage rack (excl. seat cushion)) | 1795 |

Options (extra prices)

| | | | |
|---|-----|---|-----|
| Computersupport (only for USS) | 20 | Shimano hub-dynamo DH-3D72, B&M IQ Cyo Premium T Senso Plus, B&M Line plus rear light, wired | 250 |
| Kickstand Pletscher | 25 | | |
| Tire change*: Schwalbe Marathon Plus (anti-puncture) (47 mm), Schwalbe Marathon Racer (40 mm), Big Apple (50 mm) *not all combinations are possible, check availability | 30 | SON 28 disc hub-dynamo, B&M IQ Cyo Premium T Senso Plus, B&M Line plus rear light, wired | 395 |
| Bar-end shifters for USS - 9 speed | 60 | (RAL)colour change on request | 80 |
| Bar-end shifters for USS - 10 speed | 80 | Adjustable headrest | 65 |
| Front suspension Aluminum (26 inch, not for USS) | 130 | Seat cushion swap Ventisit, 3-layer comfort type | 30 |
| Upgrade hydraulic disc brakes Shimano XT BR-M8000 F+R | 350 | Pair of low-rider supports | 60 |