

# Specifications Nazca Gaucho Tour 24" / 26" / 28"

status April 22, 2018  
Changes and errors in the prices and specifications are strictly reserved

<b>Seat height</b>	GaUCHO 24" / 26" / 28": resp. 56 / 62 / 64 cm (shock in middle position, loaded, without front suspension).
<b>Crank height</b>	GaUCHO 24" / 26" / 28": resp. 72 / 78 / 80 cm (shock in middle position, loaded, without front suspension).
<b>Wheelbase</b>	GaUCHO 24" / 26" / 28": resp. 112 / 113 / 114 cm
<b>Wheelsize</b>	24" (ETRTO 507 mm – max tire width 50 mm) // 26" (ETRTO 559 mm – max tire width 50 mm) 28" (ETRTO 622 mm – max width 40 mm )
<b>Seat angle</b>	adjustable between 26 – 34 degrees, with quick-releases
<b>Weight</b>	From ca.18 kg, depending on specification and options
<b>Material frame</b>	Frame/rear fork 25CrMo4, front tube/ connecting plates aluminium
<b>Standard accessories</b>	Alu travel rack, mud-guards, LED rear light, chain tubes
<b>Standard colours</b>	fired, applegreen, nightblue, black satin, melon yellow, white
<b>Guarantee</b>	1 year on parts, 3 years on coating, 5 years on frame. Normal wear is excluded from the guarantee.

## Technical data

	Allround 3 x 9 Dual Drive	Allround 3 x 9 Deore	Top-touring 3 x 10 Deore XT	Shimano Alfine 11 speed	Rohloff Speedhub 500/14
<b>Tires</b>	GaUCHO 2 x 24": Schwalbe Marathon HS420, 47 mm GaUCHO 2 x 26": Schwalbe Marathon HS420, 40 mm GaUCHO 2 x 28": Schwalbe Marathon HS420, 37 mm				
<b>Brakes</b>	Avid BB7 mechanical disc brakes, Avid SD7 levers				
<b>Wheels</b>	<b>front</b>	Shimano Deore / Rim ZAC2000 32h.		Shimano Deore, Rim ZAC2000 32 h	
	<b>rear</b>	Dual Drive Premium 3	Shim. Deore ZAC2000 32h	Shimano XT M785 / ZAC2000 rim 32 h	Rohloff disc / ZAC2000 32h.
<b>Rear shock</b>	DNM DV-22AR, adjustable rebound, steel spring				
<b>Front derailleur</b>	-	Deore - M591	Deore XT M781	-	-
<b>Rear derailleur</b>	SRAM X7/ Shimano Deore M591		Deore XT M781/10	Alfine chain tensioner	Rohloff chain tensioner
<b>Shifters</b>	<b>ASS/Aero</b>	SRAM X7 twist shifters or Deore SL-M590 trigger shifters		Alfine trigger shifter SL-S700	Rohloff Twist shifter
	<b>USS</b>	Shimano Dura-Ace bar-end shifters		Deore XT SL-M780 trigger	
<b>Crankset, bracket integrated</b>	FC-S501 39 or 45t. + chain guard	Shimano Deore FC-M591 48/36/26 + chain guard		Shimano Alfine FC-S501 39 or 45t. + chain guard, Integrated bracket	
<b>Cassette</b>	HG50 12-25 // 11-28 // 11-34 9 speed		M771 11-34 / 10speed	20t.	16t.
<b>Chain</b>	KMC X9-73G		KMC-X10-93S	KMC X8-93S	
<b>Front fork</b>	CrMo steel (option front suspension only for 26" ASS and AERO) 1 1/8"				
<b>Seat/cushion</b>	Material seat glasfiber/epoxy, seat type <i>Sport</i> (sizes M, L, XL) or seat type <i>Comfort</i> (sizes M, M/L, L with cushion type Comfort (Nazca) or Sport (Novosport))				

## Prices Nazca Gaucho Tour (steering options: USS, ASS, Aero)

Prices in Euro's,  
incl.21% VAT, excl.  
Shipping costs

<b>3 x 9 Allround, Shimano Deore</b>	2595
<b>3 x 9 Allround, SRAM Dual Drive 3</b>	2645
<b>3 x 10 Top touring, Shimano Deore XT-10 speed</b>	2795
<b>11 sp. Shimano Alfine hub</b>	2795
<b>14 sp. Rohloff speedhub 500/14</b>	3795
<b>Framekit</b> (consists of: frame complete, rear shock, front fork, seat with supports, steerer complete, chain idlers and tubes, luggage rack (excl. seat cushion))	1675

## Options (extra prices)

<b>Computersupport (only for USS)</b>	20	<b>Shimano hub-dynamo DH-3D72, B&amp;M IQ Cyo Premium T Senso Plus, B&amp;M Line plus rear light, wired at dynamo</b>	250
<b>Kickstand Pletscher</b>	25		
<b>Tire change*: Schwalbe Marathon Plus (anti-puncture) (47 mm), Schwalbe Marathon Racer (40 mm), Big Apple (50 mm)</b> *not all combinations are possible, check availability	30	<b>SON 28 disc hub-dynamo, B&amp;M IQ Cyo Premium T Senso Plus, B&amp;M Line plus rear light, wired at dynamo</b>	395
		<b>(RAL)colour change on request</b>	80
		<b>Short cranks 155 mm</b>	0
<b>Front suspension Aluminum (26 inch, not for USS)</b>	130	<b>Adjustable headrest</b>	65
		<b>Seat cushion swap Ventisit, 3-layer comfort type</b>	30
<b>Upgrade hydraulic disc brakes Shimano XT BR-M8000 F+R</b>	350	<b>Pair of low-rider supports</b>	60