## General specifications Nazca Pioneer up to 2018 – available as a framekit only

**Status June 2020**, Changes and errors are strictly reserved Prices in Euro's, incl. 21% VAT, excl. shipping.

	11. 0				
Seat height	57 cm (shock in middle position, loaded)				
Crank height	75 cm (shock in middle position, loaded)				
Wheelbase	110 cm				
Wheel size F+R	26" (ETRTO 559 mm – max tire width 50 mm)				
Seat angle	30-35 degrees, adjustable with quick releases				
Weight	Approx. 18 kg (depending on specification)				
Frame material	Front tube aluminum, frame and rear fork ChroMoly steel 25CrMo4				
Standard accessories	Rack, mud-guards, LED rear light, chain guard for crankset, chain tubes, stainless steel spokes and small parts.				
Standard colours	Fire red, apple green, night blue, black satin, melon yellow, white				
Guarantee	1 year on front suspension and other parts, 3 years on coating, 5 years on frame and rear fork. Normal wear is excluded from the guarantee				

Technical data gear systems (ASS, USS, AEROBAR)

reciffical data geal systems (ASS,USS, AEROBAR)							
		Allround 3x9 Dual Drive	Allround 3 x 9 Deore	Top-touring 3 x 10 Deore XT	Shimano Alfine 11 speed	Rohloff Speedhub 500/14	
Tires F+R		Schwalbe Marathon HS420, 40 mm					
Brakes		V-brakes Shimano BR-M590					
Wheels	front	Shimano Deore/ZAC2000/32 h		Chimana VT M705	Shim. Deore, ZAC2000 , 32 h		
	rear	Dual Drive 3 Zac2000/32 h	Shim. Deore ZAC2000/32 h	Shimano XT M785, ZAC2000 32 h	Alfine 11 sp/ ZAC2000 32 h	Rohloff disc/ ZAC2000 32 h	
Rear shock		DNM DV22, oil damping, nitrogen charged, steel spring (exchangeable)					
Front derailleur		n.a.	Deore-M591	Deore XT- M781	n.a.	n.a.	
Rear derailleur		Shimano Deore M591/ SRAM X7		Deore XT-M781/10	Chain tensioner Alfine	Chain tensioner Rohloff	
Type of steer		ASS: aluminum, adjustable tiller steer, cables running outside; Aerosteer: adjustable aluminium Aerosteer USS: indirect steering					
Shif- ters	ASS/AERO	Twist shifters SRAM X7 or Trigger Shimano SL-M590		Trigger shifters XT	Trigger shifter	Twist shifter	
	USS	Dura-Ace bar-e	end shifters SL-M780/10		Alfine SL-700	Rohloff	
Crankset		Alfine FC-S501 39t or 45t, bracket integrated	Shimano Deore FC-M591, 48/36/26 t + chain guard, bracket integrated		Shimano Alfine FC-S501, 39t or 45t., + chain guard, bracket integrated		
Cassette		HG50 12-25 // 11	-28// 11-34 9sp	M771 11-34 / 10 sp	20t.	16t.	
Chain		KMC X9-73G		KMC X10-93S	KMC X8-93S		
Front fork		Chroom Moly 25CrMo4 steel, 1 1/8"					
Seat/cushion		Material seat glasfiber/epoxy, seat type Sport (sizes M, L, XL) or seat type Comfort (sizes M, M/L, L with cushion type Comfort (Nazca) or Sport (Novosport)					

## The Pioneer is no longer available as a complete recumbent, framekits are still available

Framekit A frame kit consists of: frame complete, rear shock, front fork, seat with supports, steerer complete, chain idlers and tubes, luggage rack (excl. seat cushion)

€ 995

Options (prices in Euro's)				
Computersupport (only for USS)	25			
Stainless steel tiller steer, cables inside	70			
Extra idler in return chain	30			
Rear shock with adjustable rebound DV-22 AR	45			
Set low-rider supports	60			
Seat cushion Ventisit, 3 layer comfort type	75-80			
Adjustable headrest	65			
(RAL)colour change on request	80			